




Product :

SBR Rubber Tile Floor Covering

Material :

Fine grained 100% recycled tyre rubber granules bonded with polyurethane elastomer

Product Design :



Surface :

Open-Pored Smooth

Lower Side :

Dimpled

Colour(s) :

Red, Green or Black

(Small colour differences can occur due to raw material)





Dimensions / Tolerances / Weight :

Thickness(es) : 20 mm (+/- 2 mm)
Length x Width : 500 x 500 mm cm (+/- 0,8%)
Area Weight : approx. 17,7 kg/m²

Thickness(es) : 25 mm (+/- 2 mm)
Length x Width : 500 x 500 mm cm (+/- 0,8%)
Area Weight : approx. 21,0 kg/m²

Thickness(es) : 30 mm (+/- 2 mm)
Length x Width : 500 x 500 mm cm (+/- 0,8%)
Area Weight : approx. 25,0 kg/m²

Thickness(es) : 40 mm (+/- 2 mm)
Length x Width : 500 x 500 mm cm (+/- 0,8%)
Area Weight : approx. 34,0 kg/m²

Thickness(es) : 50 mm (+/- 2 mm)
Length x Width : 500 x 500 mm cm (+/- 0,8%)
Area Weight : approx. 40,0 kg/m²



Product Testing :

- Fire Resistance : Comply with the criteria of TSE (EN 71-2)
- Temperature Range : -20° C to 60° C (internal tested)
- Migration of Certain Elements : Comply with the criteria of TSE (EN 71-3)
- Phthalate Determination : Positive Result by Analysis
- Determination of Critical Fall Height : Comply with the criteria of TSE (EN 1176-1)

Results :

- 2 cm : 0,7 m
- 2,5 cm : 0,8 m
- 3 cm : 0,9 m
- 4 cm : 1,0 m
- 5 cm : 1,4 m